



We provide our customers with exceptional  
**PRODUCTS** in accordance with the highest  
international standards and also provide  
**SERVICES** that meets our customers'  
needs or exceed their expectations.

Powered by: The Prolink logo, featuring the word "PROLINK" in a bold, white, sans-serif font. A white swoosh underline starts under the "P", goes under the "O", and then curves around the "L" and "I" before ending under the "K".

## Description







ProLink 2 Port UK type Faceplate W/Shutter & Station 2 ID 86\*86

## British Faceplate

Suitable for RJ45 connection modules, connection module ISDN 2 xRJ45



## Features

-  Suitable for flush mounting as well as duct-mounted installations
-  Surface mounting compliant with the US mounting box
-  Dimensions for back boxes and floor box module holders of 83.5 mm (3.29 inch) mounting tracks
-  Ready for the PROLINK security system
-  Supplied with label windows plus exchangeable label strips
-  Recommended depth for back boxes and floor boxes  $\geq 70$  mm

## Technical Data

<b>Outlet type</b>	Faceplate
<b>Application area</b>	Flush-mounting (FM)
<b>Capacity (ports)</b>	2
<b>Color</b>	White
<b>Assembly</b>	empty
<b>Dimensions</b>	86*86 mm
<b>Material</b>	plastic: PC + ABS
<b>Weight</b>	33 G

## Mechanical Characteristics

## Environmental Characteristics

Plug Tolerances and Dimensions	Operating Temperature
Compliant IEC 60603-7	-10°C to -60°C